



TRAILER SPECIFICATIONS AND STANDARD FEATURES

5 Wide True-Line Trailers:

	True-Line 5 x 8 V	True-Line 5 x 10 V	True-Line 5 x 12 V
Body Length	10'1"	11'7"	13'7"
Body Width	5'	5'	5'
Overall Length	12'	13'6"	15'6"
Overall Width	6'10"	6'10"	6'10"
Overall Height	7'3"	7'3"	7'3"
Interior Length	9'11"	11'5"	13'5"
Interior Width	57"	57"	57"
Interior Height	5'6"	5'6"	5'6"
Axle	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2"	2"
Connector	4-Way	4-Way	4-Way
Curb Weight	910	965	995
GVWR	2750	2750	2750
GAWR	2500	2500	2500
Est. Payload	1840	1785	1755
Rear Door Width	52 1/2"	52 1/2"	52 1/2"
Rear Door Height	63"	63"	63"

- Rubber Torsion Axle
- Tube Main Frame
- Flat Roof – V Front
- Steel Corners – V and Front
- Full Height X Members
- Radial Tires Load Range C
- Seamless Aluminum Roof
- LED Exterior Lighting
- ¼" Lauan Plywood Sidewalls
- ¾" Plywood Floor
- Aluminum Fenders
- Aluminum Tread Plate Stone Guard
- Double Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock