



TRAILER SPECIFICATIONS AND STANDARD FEATURES

7 Wide Single and Tandem Axles True-Line Trailers:

	True-Line 7 X 12 V	True-Line 7x12 V - T	True-Line 7x14 V - T	True-Line 7x16 V - T
Body Length	14'1"	14'1"	16'1"	18'1"
Body Width	84"	84"	84"	84"
Overall Length	16'	16'	18'	20'
Overall Width	102"	102"	102"	102"
Overall Height	7'10"	7'10"	7'10"	7'10"
Interior Length	13'11"	13'11"	15'11"	17'11"
Interior Width	81"	81"	81"	81"
Interior Height	6' 6"	6' 6"	6' 6"	6' 6"
Axle	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way
Curb Weight	1700	1925	2025	2125
GVWR	3500	7700	7700	7700
GAWR (T = x 2)	3500	3500	3500	3500
Est. Payload	1800	5775	5675	5575
Rear Door Width	76 1/2"	76 1/2"	76 1/2"	76 1/2"
Rear Door Height	74"	74"	74"	74"

- Rubber Torsion Axle
- Tube Main Frame
- Flat Roof – V Front
- Steel Corners – V and Front
- Full Height X Members
- Radial Tires Load Range C
- Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Plywood Floor
- Aluminum Tread Plate Stone Guard
- Double Rear Doors
- Aluminum Fenders
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.