



TRAILER SPECIFICATIONS AND STANDARD FEATURES

8 Wide 10K Tandem Axle:

	ITI 8X12 -T- 10K	ITI 8X16 -T- 10K	ITI 8X18 -T- 10K	ITI 8X20 -T- 10K	ITI 8X24 -T- 10K
Body Length	12'	16'	18'	20'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	16'	20'	22'	24'	28'
Overall Width	102"	102"	102"	102"	102"
Overall Height	8'6"	8'6"	8'6"	8'6"	8'6"
Interior Length	11'9"	15'9"	17'9"	19'9"	23'9"
Interior Width	95"	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	81"	81"	81"	81"	81"
Axle	Torsion	Torsion	Torsion	Torsion	Torsion
Tire	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15
Wheel	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way	7-Way
Curb Weight	2415	2715	2855	2990	3320
GVWR	10000	10000	10000	10000	10000
GAWR (x2)	5200	5200	5200	5200	5200
Est. Payload	7585	7285	7145	7010	6680
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68 1/2"	68 1/2"	68 1/2"	68 1/2"	68 1/2"

- Rubber Torsion Axles
- Tube Main Frame
- Full Height X Members
- Radial Tires Load Range D
- 22 AH Full Size Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Plywood Floor
- Side Door
- Aluminum Tread Plate Stone Guard
- Anodized Top and Bottom Trim
- Double Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.