



TRAILER SPECIFICATIONS AND STANDARD FEATURES

8 Wide Tandem Axle:

	ITI 8 X 12 - T	ITI 8 X 16 - T	ITI 8 X 18 - T	ITI 8 X 20 - T	ITI 8 X 24 - T
Body Length	12'	14'	18'	20'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	16'	20'	22'	24'	28'
Overall Width	102"	102"	102"	102"	102"
Overall Height	8'5"	8'5"	8'5"	8'5"	8'5"
Interior Length	11'9"	15'9"	17'9"	19'9"	23'9"
Interior Width	95"	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	83"	83"	83"	83"	83"
Axle	Torsion	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way	7-Way
Curb Weight	2090	2380	2530	2680	2975
GVWR	7700	7700	7700	7700	7700
GAWR (x2)	3500	3500	3500	3500	3500
Est. Payload	5610	5320	5170	5020	4725
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68 1/2"	68 1/2"	68 1/2"	68 1/2"	68 1/2"

- Rubber Torsion Axles
- Tube Main Frame
- Full Height X Members
- Radial Tires Load Range C
- 22 AH Full Size Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Plywood Floor
- Side Door
- Aluminum Tread Plate Stone Guard
- Anodized Top and Bottom Trim
- Double Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.