



**TRAILER SPECIFICATIONS AND STANDARD FEATURES**

**SPECIALTY 8 Wide Trailers:**

	ITI 8X20-T-BT	ITI 8X20-T-10K-BT	ITI 8X24 -T- BT	ITI 8X24 -T- 10K - BT
Body Length	20'	20'	24'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	24'	24'	28'	28'
Overall Width	102"	102"	102"	102"
Overall Height	8'5"	8'6"	8'5"	8'6"
Interior Length	19'9"	19'9"	23'9"	23'9"
Interior Width	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	83"	81"	83"	81"
Axle	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST225/75R15	ST205/75R15	ST225/75R15
Wheel	15" - 5 Bolt	15" - 6 Bolt	15" - 5 Bolt	15" - 6 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way
Curb Weight	3100	3260	3500	3660
GVWR	7700	10000	7700	10000
GAWR (x2)	3500	5200	3500	5200
Est. Payload	4600	6740	4200	6340
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68 1/2"	68 1/2"	68 1/2"	68 1/2"

- Rubber Torsion Axles
- Tube Main Frame
- Full Height X Members
- 4' Beavertail
- 22 AH Full Size Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Plywood Floor
- Aluminum Tread Plate Stone Guard
- Anodized Top and Bottom Trim
- Ramp Door – Side Door
- Aluminum Cam Bar Lock
- Aluminum Door Hinges

Specifications and features subject to change without notice.