



LANDSCAPE TRAILER SPECIFICATIONS AND STANDARD FEATURES

	ITI 7x12-T-LS	ITI 7x14-T-LS	ITI 7x16-T-LS
Body Length	12'	14'	16'
Body Width	84"	84"	84"
Overall Length	16'	18'	20'
Overall Width	102"	102"	102"
Overall Height	7'10"	7'10"	7'10"
Interior Length	11'9"	13'9"	15'9"
Interior Width	81"	81"	81"
Interior Height	6'6"	6'6"	6'6"
Axle	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way
Curb Weight	1885	1985	2080
GVWR	3500	7700	7700
GAWR (T = x 2)	3500	3500	3500
Est. Payload	5815	5715	5620
Rear Door Width	76 1/2"	76 1/2"	76 1/2"
Rear Door Height	69"	69"	69"

	ITI 8x12-T-LS	ITI 8x16-T-LS	ITI 8x18-T-LS	ITI 8x20-T-LS	ITI 8x24-T-LS
Body Length	12'	14'	18'	20'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	16'	20'	22'	24'	28'
Overall Width	102"	102"	102"	102"	102"
Overall Height	8'5"	8'5"	8'5"	8'5"	8'5"
Interior Length	11'9"	15'9"	17'9"	19'9"	23'9"
Interior Width	95"	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	83"	83"	83"	83"	83"
Axle	Torsion	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way	7-Way
Curb Weight	2090	2380	2530	2680	2975
GVWR	7700	7700	7700	7700	7700
GAWR (x2)	3500	3500	3500	3500	3500
Est. Payload	5610	5320	5170	5020	4725
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68 1/2"	68 1/2"	68 1/2"	68 1/2"	68 1/2"

	ITI 8X12-T-10K-LS	ITI 8X16-T-10K-LS	ITI 8X18-T-10K-LS	ITI 8X20-T-10K-LS	ITI 8X24-T-10K-LS
Body Length	12'	16'	18'	20'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	16'	20'	22'	24'	28'
Overall Width	102"	102"	102"	102"	102"
Overall Height	8'6"	8'6"	8'6"	8'6"	8'6"
Interior Length	11'9"	15'9"	17'9"	19'9"	23'9"
Interior Width	95"	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	81"	81"	81"	81"	81"
Axle	Torsion	Torsion	Torsion	Torsion	Torsion
Tire	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15	ST225/75R15
Wheel	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt	15" - 6 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way	7-Way
Curb Weight	2415	2715	2855	2990	3320
GVWR	10000	10000	10000	10000	10000
GAWR (x2)	5200	5200	5200	5200	5200
Est. Payload	7585	7285	7145	7010	6680
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68 1/2"	68 1/2"	68 1/2"	68 1/2"	68 1/2"

- Rubber Torsion Axles
- Tube Main Frame
- Full Height X Members
- X Members on 16" Center Behind A Frame
- 22 AH Full Size Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Pressure Treated Plywood Floor
- Loose Material Diverter Between Floor and Walls
- Aluminum Fenders
- ATP Stone Guard
- Exterior Mounted Spare Tire and Cover
- Anodized Top and Bottom Trim
- Ramp Door – Side Door
- Aluminum Door Hinges
- Aluminum Cam Bar Locks
- First Aid Kit