



TRAILER SPECIFICATIONS AND STANDARD FEATURES

5 Wide Pride Line Trailers:

	Pride Line 5 x 8	Pride Line 5 x 10	Pride Line 5 x 12
Body Length	8'3"	10'	12'
Body Width	5'	5'	5'
Overall Length	12'	13'6"	15'6"
Overall Width	6'10"	6'10"	6'10"
Overall Height	7'3"	7'3"	7'3"
Interior Length	8'	9'9"	11'9"
Interior Width	57"	57"	57"
Interior Height	5'6"	5'6"	5'6"
Axle	Spring	Spring	Spring
Tire	ST205/75D15	ST205/75D15	ST205/75D15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2"	2"
Connector	4-Way	4-Way	4-Way
Curb Weight	910	965	995
GVWR	2995	2995	2995
GAWR	3500	3500	3500
Est. Payload	2085	2030	2000
Rear Door Width	52 1/2"	52 1/2"	52 1/2"
Rear Door Height	57"	57"	57"

- Tube Main Frame
- Round Roof
- Steel Corners
- Full Height X Members – 24” OC
- Bias Ply 15” Tires Load Range C
- Seamless Aluminum Roof
- LED Exterior Lighting
- ¼” Lauan Plywood Sidewalls
- ¾” Plywood Floor
- Aluminum Fenders
- Aluminum Tread Plate Stone Guard
- Single Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.