



TRAILER SPECIFICATIONS AND STANDARD FEATURES

6 Wide Pride Line Trailers:

| | Pride Line 6 x 10 | Pride Line 6 x 12 |
|------------------|-------------------|-------------------|
| Body Length | 10' | 12' |
| Body Width | 6' | 6' |
| Overall Length | 14' | 16' |
| Overall Width | 7'10" | 7'10" |
| Overall Height | 7'9" | 7'9" |
| Interior Length | 9'9" | 11'9" |
| Interior Width | 69" | 69" |
| Interior Height | 6' | 6' |
| Axle | Spring | Spring |
| Tire | ST205/75D15 | ST205/75D15 |
| Wheel | 15" - 5 Bolt | 15" - 5 Bolt |
| Hitch Ball | 2" | 2" |
| Connector | 4-Way | 4-Way |
| Curb Weight | 990 | 1190 |
| GVWR | 2995 | 2995 |
| GAWR | 3500 | 3500 |
| Est. Payload | 2005 | 1805 |
| Rear Door Width | 64 1/2" | 64 1/2" |
| Rear Door Height | 63" | 63" |

- Tube Main Frame
- Round Roof
- Steel Corners
- Full Height X Members – 24” OC
- Bias Ply 15” Tires Load Range C
- Seamless Aluminum Roof
- LED Exterior Lighting
- ¼” Lauan Plywood Sidewalls
- ¾” Plywood Floor
- Aluminum Fenders
- Aluminum Star Brite Stone Guard
- Aluminum Bottom Trim
- Double Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.