



TRAILER SPECIFICATIONS AND STANDARD FEATURES

7 Wide Single and Tandem Axles Pride Line Trailers:

| | Pride Line 7 X 12 | Pride Line 7x12 - T | Pride Line 7x14 - T | Pride Line 7x16 - T |
|------------------|-------------------|---------------------|---------------------|---------------------|
| Body Length | 12' | 12' | 14' | 16' |
| Body Width | 84" | 84" | 84" | 84" |
| Overall Length | 16' | 16' | 18' | 20' |
| Overall Width | 102" | 102" | 102" | 102" |
| Overall Height | 8'4" | 8'4" | 8'4" | 8'4" |
| Interior Length | 11'9" | 11'9" | 13'9" | 15'9" |
| Interior Width | 81" | 81" | 81" | 81" |
| Interior Height | 6' 6" | 6' 6" | 6' 6" | 6' 6" |
| Axle | Torsion | Torsion | Torsion | Torsion |
| Tire | ST205/75D15 | ST205/75D15 | ST205/75D15 | ST205/75D15 |
| Wheel | 15" - 5 Bolt | 15" - 5 Bolt | 15" - 5 Bolt | 15" - 5 Bolt |
| Hitch Ball | 2" | 2 5/16" | 2 5/16" | 2 5/16" |
| Connector | 7-Way | 7-Way | 7-Way | 7-Way |
| Curb Weight | 1620 | 1720 | 1985 | 2095 |
| GVWR | 3500 | 7700 | 7700 | 7700 |
| GAWR (T = x 2) | 3500 | 3500 | 3500 | 3500 |
| Est. Payload | 1880 | 5920 | 5715 | 5605 |
| Rear Door Width | 76 1/2" | 76 1/2" | 76 1/2" | 76 1/2" |
| Rear Door Height | 68" | 68" | 68" | 68" |

- Rubber Torsion Axle
- Tube Main Frame
- Round Roof
- Steel Corners
- Full Height X Members – 24” OC
- Bias Ply 15” Tires Load Range C
- Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8” Plywood Sidewalls
- 3/4” Plywood Floor
- Aluminum Star Brite Stone Guard
- Double Rear Doors
- Side Door
- Aluminum Fenders
- Aluminum Door Hinges and Aluminum Cam Bar Lock

Specifications and features subject to change without notice.