



TRAILER SPECIFICATIONS AND STANDARD FEATURES

8 Wide Pride Line Tandem Axle:

	Pride Line 8 X 16 - T	Pride Line 8 X 18 - T	Pride Line 8 X 20 - T	Pride Line 8 X 24 - T
Body Length	16'	18'	20'	24'
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	21'	23'	25'	29'
Overall Width	102"	102"	102"	102"
Overall Height	8'5"	8'5"	8'5"	8'5"
Interior Length	15'9"	17'9"	19'9"	23'9"
Interior Width	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	83"	83"	83"	83"
Axle	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75D15	ST205/75D15	ST205/75D15	ST205/75D15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way
Curb Weight	2325	2450	2650	2975
GVWR	7700	7700	7700	7700
GAWR (x2)	3500	3500	3500	3500
Est. Payload	5375	5250	5050	4725
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	68"	68"	68"	68"

- Rubber Torsion Axles
- Tube Main Frame
- Round Roof
- Steel Corners
- Full Height X Members – 24” OC
- Bias Ply Tires Load Range C
- Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8” Plywood Sidewalls
- 3/4” Plywood Floor
- Aluminum Tread Plate Stone Guard
- Rear Ramp Door with Spring Assist and Stabilizer Jacks
- C/S Side Door
- Aluminum Door Hinges and Aluminum Cam Bar Lock

Specifications and features subject to change without notice.