



STOCK-AIDE

TRAILER SPECIFICATIONS AND STANDARD FEATURES

5 Wide STOCK-AIDE Trailers:

	WW 5 x 8 V	WW 5 x 10 V	WW 5 x 12 V
Body Length	9'	10'6"	12'6"
Body Width	5'	5'	5'
Overall Length	12'	13'6"	15'6"
Overall Width	6'10"	6'10"	6'10"
Overall Height	7'	7'	7'
Interior Length	8'9"	10'3"	12'3"
Interior Width	57"	57"	57"
Interior Height	5'6"	5'6"	5'6"
Axle	Spring	Spring	Spring
Tire	ST205/75D15	ST205/75D15	ST205/75D15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2"	2"
Connector	4-Way	4-Way	4-Way
Curb Weight	820	900	
GVWR	2990	2990	2990
GAWR	3500	3500	3500
Est. Payload	2170	2090	
Rear Door Width	52 1/2"	52 1/2"	52 1/2"
Rear Door Height	63"	63"	63"

- Spring Axle
- Tube Main Frame
- Flat Roof – V Front – 12"
- C Cross Members
- Steel Belted Tires Load Range C – 15"
- Seamless Aluminum Roof
- LED Exterior Lighting
- 1/4" Lauan Plywood Sidewalls
- 3/4" Flooring
- Aluminum Fenders
- Aluminum Star Brite Splash Guard
- Single Rear Door
- .024 White Aluminum Standard
- LED Tail Lights
- 12V Interior Junction Box