



STOCK-AIDE

TRAILER SPECIFICATIONS AND STANDARD FEATURES

6 Wide STOCK-AIDE Trailers:

	WW 6 x 10 V	WW 6 x 12 V
Body Length	11'3"	13'3"
Body Width	6'	6'
Overall Length	14'	16'
Overall Width	7'10"	7'10"
Overall Height	7'8"	7'8"
Interior Length	11'	13'
Interior Width	69"	69"
Interior Height	6'	6'
Axle	Spring	Spring
Tire	ST205/75D15	ST205/75D15
Wheel	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2"
Connector	4-Way	4-Way
Curb Weight	950	1020
GVWR	2995	2995
GAWR	3500	3500
Est. Payload	2045	1975
Rear Door Width	64 1/2"	64 1/2"
Rear Door Height	69"	69"

- Spring Axle
- Tube Main Frame
- Flat Roof – V Front – 15”
- C Cross Members
- Steel Belted Tires Load Range C – 15”
- Seamless Aluminum Roof
- LED Exterior Lighting
- ¼” Lauan Plywood Sidewalls
- ¾” Flooring
- Aluminum Fenders
- Aluminum Star Brite Splash Guard
- Double Rear Doors
- 30” Bar Lock Side Door
- .024 White Aluminum Standard
- LED Tail Lights
- 12V Interior Junction Box