



STOCK-AIDE

TRAILER SPECIFICATIONS AND STANDARD FEATURES

7 Wide Single and Tandem Axles STOCK-AIDE Trailers:

	WW 7 X 12 V	WW 7x12 V - T	WW 7x14 V - T	WW 7x16 V - T
Body Length	13'6"	13'6"	15'6"	17'6"
Body Width	84"	84"	84"	84"
Overall Length	16'	16'	18'	20'
Overall Width	102"	102"	102"	102"
Overall Height	7'6"	7'6"	7'6"	7'6"
Interior Length	13'2"	13'2"	15'2"	17'2"
Interior Width	81"	81"	81"	81"
Interior Height	6'	6'	6'	6'
Axle	Spring	Spring	Spring	Spring
Tire	ST205/75D15	ST205/75D15	ST205/75D15	ST205/75D15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way
Curb Weight	1320	1765	1985	2080
GVWR	3500	7700	7700	7700
GAWR (T = x 2)	3500	3500	3500	3500
Est. Payload	2180	5935	5715	5620
Rear Door Width	76 1/2"	76 1/2"	76 1/2"	76 1/2"
Rear Door Height	69"	69"	69"	69"

- Spring Axle
- Tube Main Frame
- Flat Roof – V Front – 18"
- C Cross Members
- Steel Belted Tires Load Range C – 15"
- Seamless Aluminum Roof
- LED Exterior Lighting
- 1/4" Lauan Plywood Sidewalls
- 3/4" Flooring
- Aluminum Fenders
- Aluminum Star Brite Splash Guard
- Double Rear Doors
- 30" Bar Lock Side Door
- .024 White Aluminum Standard
- LED Tail Lights
- 12V Interior Junction Box