



TRAILER SPECIFICATIONS AND STANDARD FEATURES

6 Wide True-Line Trailers:

	True-Line 6 x 10 V	True Line 6 x 12 V
Body Length	11'9"	13'9"
Body Width	6'	6'
Overall Length	14'	16'
Overall Width	7'10"	7'10"
Overall Height	7'9"	7'9"
Interior Length	11'7"	13'7"
Interior Width	69"	69"
Interior Height	6'	6'
Axle	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2"	2"
Connector	4-Way	4-Way
Curb Weight	995	1250
GVWR	2995	2995
GAWR	3500	3500
Est. Payload	2000	1745
Rear Door Width	64 1/2"	64 1/2"
Rear Door Height	68"	68"

- Rubber Torsion Axle
- Tube Main Frame
- Flat Roof V Front
- Steel Corners – V and Front
- Full Height X Members
- Radial Tires Load Range C
- Seamless Aluminum Roof
- LED Exterior Lighting
- ¼” Lauan Plywood Sidewalls
- ¾” Plywood Floor
- Aluminum Fenders
- Aluminum Tread Plate Stone Guard
- Anodized Top and Bottom Trim
- Double Rear Doors
- Aluminum Door Hinges
- Aluminum Cam Bar Lock

Specifications and features subject to change without notice.