



TRAILER SPECIFICATIONS AND STANDARD FEATURES

8 Wide True-Line Tandem Axle:

	True-Line 8 X 16 - V - T	True-Line 8 X 18 - V - T	True-Line 8 X 20 - V - T	True-Line 8 X 24 - V - T
Body Length	18'3"	20'3"	22'3"	26'3"
Body Width	98 1/4"	98 1/4"	98 1/4"	98 1/4"
Overall Length	21'	23'	25'	29'
Overall Width	102"	102"	102"	102"
Overall Height	8'5"	8'5"	8'5"	8'5"
Interior Length	17'9"	19'9"	21'9"	25'9"
Interior Width	95"	95"	95"	95"
Interior Height	6'6"	6'6"	6'6"	6'6"
Wheel Box Clearance	83"	83"	83"	83"
Axle	Torsion	Torsion	Torsion	Torsion
Tire	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt	15" - 5 Bolt
Hitch Ball	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Connector	7-Way	7-Way	7-Way	7-Way
Curb Weight	2625	2685	2750	3050
GVWR	7700	7700	7700	7700
GAWR (x2)	3500	3500	3500	3500
Est. Payload	5075	5015	4950	4650
Rear Door Width	91 1/2"	91 1/2"	91 1/2"	91 1/2"
Rear Door Height	74"	74"	74"	74"

- Rubber Torsion Axles
- Tube Main Frame
- Flat Roof – V Front
- Steel Corners – V and Front
- Full Height X Members
- Radial Tires Load Range C
- Battery for Breakaway System
- Seamless Aluminum Roof
- LED Exterior Lighting
- 3/8" Plywood Sidewalls
- 3/4" Plywood Floor
- Aluminum Tread Plate Stone Guard
- Rear Ramp Door with Spring Assist and Stabilizer Jacks
- C/S Side Door
- Aluminum Door Hinges and Aluminum Cam Bar Lock

Specifications and features subject to change without notice.